



## ENDOSCOPE SEARCH KITS

### NON-CONDUCTIVE FLEXIBLE ENDOSCOPE KIT



#### **MQIFE.06.0.1500.000.060. A. Flexible Endoscope.**

- 6mm diameter by 1500mm working length.
- High resolution image guide.
- Fuel/watertight shaft with crush resistant, tested to 350 kilos, over 100mm section.
- Viton outer with Viton tip bending section.
- Fixed tip, non-conductive with non-metallic shaft and tip section, non-sparking.
- 4 way +/- 140° remote end tip articulation.
- Ergonomic handgrip, with starwheel controls, dioptré focus adjustment.
- 0° direct forward direction of view, 60° field of view. Focus preset, depth 10mm-infinity.
- Integral 1.5 metre long lightguide cable, with BS/ACMI male lightsource connector. BS.31.75mm solid tapered eyecup, photo adaptable.

#### **LSB. 24. Compact High Intensity Lightsource.**

- 24watts miniature metal halide arc lamp. Low voltage 12vDC.
- 30 million lux. 350 hour average lamp life.
- Cool running. 5,500° K daylight, high colour temperature lamp.
- BS/ACMI lightguide boss. Mechanical iris shutter light control.
- Compact size 114 x 84 x 84 mm. Weight 0.7 kilo.

#### **LSB.24/B Battery Belt and Charger.**

- Adjustable waist-belt with separate lightsource pouch and battery pouches.
- Integral 8.2Ah 12vDC SLA rechargeable battery pack and separate charger 240v Ac. 50 Hz.

All 'Endoscan' endoscopes are manufactured in the UK.

**Endoscan Marketing Ltd. 58 Acacia Road, St Johns Wood. London. UK. NW8. 6AG.**

Telephone Direct: 44 (0)207 483 2300. Sales: 44 (0)1258 450523. Switchboard: 44 (0)207 483 2281.

Facsimile: Direct: 44 (0)207 483 2900. Sales: 44 (0)1258 450523.

E-mail: sales@endoscan.co.uk Website: www.endoscan.co.uk