

## HYDRA PIPE CAMERA SYSTEM



ISO 9001 CERTIFIED ORGANISATION



Cert No. 94030

Inspection Optics Ltd  
Garston Bridge, Garsdale  
Frome, Somerset. BA11 1RU

Phone: 01373 466147

Fax: 01373 466072

enquiries@inspectionoptics.co.uk

www.inspectionoptics.co.uk

**HYDRA PORTABLE PIPE CAMERA SYSTEM**  
*20, 32 & 50mm diameter colour camera head on  
10 metres of rigidised cable or up to  
30 metre fully flexible cable.  
Camera head and cable fully watertight.*

*Ideal for inspection of pipe work or long narrow  
lengths of ducting. Being fully portable can be used  
for inspection in difficult access areas.*

## CAMERA SPECIFICATIONS

### **HYDRA-CC**

Ruggedised carry case with high density foam cut outs for storage of camera heads, cable, charger and mains input socket 110-260VAC. Lid holds 15" LCD monitor and integral 11A Li Ion battery pack. Supplied complete with 10 metres of fully flexible cable ( for 32 and 50mm dia cameras only.) and battery charger.

### **STANDARD CAMERA OPTIONS:**

#### **HYDRA 20**

20mm dia by 32mm long delryn housed CMOS 1/5" colour Camera 240 TV lines 2 lux minimum illumination with 6 white light LED's 60° field of view lens. Rigidised or fully flexible fitted cable 15 metres long.. (Fully submersible)

#### **HYDRA 32**

32mm dia by 108mm long delryn housed 1/4" 450 TV lines 1.6 lux minimum illumination colour CCD camera. Featuring 9 white light LED's, 54° field of view lens. Watertight connector for fitment to either rigidised or fully flexible cable. (Fully submersible)

#### **HYDRA 50**

50mm dia by 125mm long delryn housed 1/4" 450 TV lines 1.6 lux minimum illumination colour CCD camera. Featuring 9 + 6 white light LED's, 120° field of view lens. Watertight connector for fitment to either rigidised or fully flexible cable. (Fully submersible)

Other camera variations available to suit customer requirements. Please contact office for details.

**NOTE: SPECIFICATIONS MAY CHANGE WITHOUT PRIOR NOTIFICATION**

