

NEW

TECAM-3 USB
fully automatic USB
video camera with VIPAQ™ technique

The first fully automatic USB video camera especially for technical endoscopic applications, with remote control of all important functions, extremely compact and light weight



- ◆ extremely high dynamic because of the combined shutter and gain automatic
- ◆ no separate video processor required
- ◆ fatigue-free inspections because of the exceptional ergonomic design and extreme light weight
- ◆ remote control buttons for the control of all important functions direct on the camera head
(picture freezing, picture storage, sensitivity control, autom. white balance)
- ◆ direct USB output
- ◆ additionally S-Video and remote cable outputs
- ◆ easy to understand image management software with further functions, easy to install
- ◆ Scope of supply: camera with 3 m cable, power supply for S-Video use, driver and management software on USB drive, cleaning kit

Picture sensor / objective connection	1/2" CCD / C-mount thread
Video resolution	752 x 582 pixels / PAL: 460 lines (h) / NTSC: 470 lines (h)
Colour system / TV norm	PAL / 625 lines (50Hz) or NTSC / 525 lines (60Hz)
Sensitivity adjustment / min. sensitivity	automatically in 5 preselected steps / 1,0 Lux (F=1,2)
Standards / EMC	CE EN/IEC 55011, A1, A2, EN/IEC 61000-6-2 / 89/336/EWG, 93/68/EWG
Order numbers for compl. kit (without lense)	PAL: 2 55300 0011 NTSC: 2 55300 7011

X.08.GB6

TECAM3-USB



VisionScope Technologies

Tel: 01223 655740. Fax: 01954 211535

Email: info@vst.org.uk Web: www.vst.org.uk