

ENDOSCOPE SEARCH KITS

NON-CONDUCTIVE FLEXIBLE ENDOSCOPE KIT



MQIFE.06.0.1500.000.060. A. Flexible Endoscope.

- 6mm diameter by 1500mm working length.
- High resolution image guide.
- Fuel/watertight shaft with crush resistant, tested to 350 kilos, over 100mm section.
- Viton outer with Viton tip bending section.
- Fixed tip, non-conductive with non-metallic shaft and tip section, non-sparking.
- 4 way +/- 140° remote end tip articulation.
- Ergonomic handgrip, with starwheel controls, dioptre focus adjustment.
- 0° direct forward direction of view, 60° field of view. Focus preset, depth 10mm-infinity.
- Integral 1.5 metre long lightguide cable, with BS/ACMI male lightsource connector. BS.31.75mm solid tapered eyecup, photo adaptable.

LSB. 24. Compact High Intensity Lightsource.

- 24watts miniature metal halide arc lamp. Low voltage 12vDC.
- 30 million lux. 350 hour average lamp life.
- Cool running. 5,500° K daylight, high colour temperature lamp.
- BS/ACMI lightguide boss. Mechanical iris shutter light control.
- Compact size 114 x 84 x 84 mm. Weight 0.7 kilo.

LSB.24/B Battery Belt and Charger.

- Adjustable waist-belt with separate lightsource pouch and battery pouches.
- Integral 8.2Ah 12vDC SLA rechargeable battery pack and separate charger 240v Ac. 50 Hz.

Moritex-Schott (Schott UK Ltd)

www.moritex.com

info@moritex.com

Tel: 01223 813322

Fax: 01223 813352